



RBZ

AUTOMATIC STUD FEEDER

FOR WELDING ELEMENTS WITHOUT FLANGE

MODERN DESIGN WITH
ALUMINIUM PROFILE TECHNOLOGY

BELT BUNKER
(CAPACITY 10 KG / 5 L)

EASY OPERATION

ROBUST HOUSING FOR NOISE
REDUCTION AND AS
PROTECTION AGAINST DIRT
AND WELDING SPATTERS

SECURE DETECTION
OF STUD POSITION

CHANGEABLE CONVERSION KITS
FOR STUD DIAMETERS 4-12 MM



APPLICABLE WITH ALL AUTOMATIC WELDING HEADS AND GUNS

The RBZ is a feeder for the fully automatic feeding of welding elements into automatic stud welding heads and automatic stud welding guns. With the RBZ welding elements without flange can be fed fast, safe and easy.

It distinguishes itself through very easy operation as well as fast and easy retooling to different stud diameters.

TECHNICAL DATA AND CHARACTERISTICS

	RBZ
Stud diameter	Ø 4-12 mm (other Ø on inquiry)
Stud length	8-50 mm
Stud type	welding elements without flange
Feeding capacity	up to 25 studs/minute (depending on stud diameter and length)
Maximum filling quantity	10 kg / 5 l (belt bunker)
Compressed air connection	6 bar
Mains supply	230 V, 50 Hz
Mains plug	earth contact plug according to DIN 49441
Dimensions	
Width (mm)	450
Height (mm)	770
Length (mm)	650
Weight (kg)	55



Bolte GmbH

Flurstraße 25
D-58285 Gevelsberg

Tel.: +49 (0)2332 55106-0
Fax: +49 (0)2332 55106-11

Ohmstraße 3
D-85221 Dachau

Tel.: +49 (0)8131 5159-0
Fax: +49 (0)8131 5159-11

E-Mail: info@bolte.gmbh



www.bolte.gmbh